

NATIONAL ACADEMY OF SCIENCES OF UKRAINE

H. V. KARPENKO PHYSICO-MECHANICAL INSTITUTE

PHYSICO-CHEMICAL MECHANICS OF MATERIALS

International Scientific-Technical Journal

Founded in January 1965

Published bimonthly

VOLUME 42, № 6, 2006

November – December

CONTENTS

- Kuryliak D. B., Nazarchuk Z. T., and Voitko M. V.* The analysis of the field of SH-wave scattered by a finite crack at the materials interface 5
- SUMMARY.* The problem of SH elastic plane wave diffraction for an finite width crack located at the plane interface between two dissimilar elastic perfectly joined isotropic materials was analysed. The problem is formulated in terms of the Wiener-Hopf equation. An approximate solution of such equation is proposed. Also the numerical calculation results for a wide band frequency range are presented for diffracted far field patterns. The peculiarities of the far field distribution at the critical angle directions as well as the lateral wave excitation are analyzed. The probability of the defect detection is discussed and the simple experimental scheme of the test stand for NDT crack width evaluation based on the field displacement modulus measuring at the critical angle area is proposed.
- Savruk M. P., Kazberuk A.* Relation between stress intensity and concentration factors for sharp and rounded V-shaped notches 17
- SUMMARY.* The solution of elastostatics problem for a plane with an infinite rounded V-shaped notch is obtained by a singular integral equation method. This solution is used to find relation between stress intensity factor at the tip in a sharp V-notch, stress concentration factor for rounded V-notch, and radius of curvature in the notch vertex. It is shown that such dependence is ambiguous: for the same curvature at the notch vertex it is different for different shapes of its vicinity.
- Kushnir R. M. and Soliar T. Ya.* Quasi-static temperature stresses in multiply-connected plates under their heating 27
- SUMMARY.* An algorithm for determination of quasi-static temperature stresses in multiply connected plates with heat transfer, heated by the heat sources, is presented. The Laplace transform, refined formulas of its numerical conversion, and method of integral equations are used for solution of the problem. Calculation of non-stationary temperatures and stresses in plates of different shape, caused by the temperatures, is considered.
- Monastyrskyi B. Ye.* A method for determining contact compliance of bodies with surface grooves 34
- SUMMARY.* An axially symmetric model of an elastic incomplete contact of a semi-infinite isotropic half-space and a rigid substrate with a set of uniformly distributed surface penny-shaped grooves is developed. The model takes into account the total influence of the conglomerate of surface defects on the stress-strain state in the vicinity of a separate inhomogeneity. The method of determination of the integral elastic rigidity of the contact surface is proposed. Comparative analysis of the obtained results with that known in literature is carried out on the basis of the proposed approach with the known solutions of 3D problems.
- Popovych V. S., Harmatii H. Yu., and Vovk O. M.* Thermoelastic state of a thermosensitive hollow sphere during convective-radiant heat-transfer with environment 39
- SUMMARY.* The solution is constructed for the non-stationary heat conduction problem for a thermosensitive hollow sphere with convective-radiant heat exchange with the surroundings of constant temperature. In addition it is assumed that heat-exchange coefficients and degrees of the surfaces darkness also depend on the temperature. The effect of the sphere material thermosensitivity on the value and character of temperature distribution and components of the stress-strain state is studied.
- Ivanova T., Zicans J., Kalnins M., Maksimov R., and Roja Ž.* Thermoplastic multiphase composites: tensile and creep behaviour 49

Mirkin L. I., <u>Shesterikov S. A.</u> , Yumashev M. V., and Yumasheva M. A. Nonstability of thermal fracture under constrained deformation	55
---	----

SUMMARY. Quasi-static deformation and fracture of brittle solids in unstable temperature conditions is considered. Fracture criterion is the achievement of critical stress values. The stress state and crack propagation were calculated under assumption that new-formed surfaces are stress-free while at the crack tips the condition of fracture criterion is fulfilled. It is shown that in the wide range of thermomechanical loading the failure process is unstable, that is, when the threshold value is achieved at some point of a body a crack instantly propagates to the critical size, which corresponds to the new stability state. It is shown that mechanical overloading of the specimen can significantly suppress the effect of instability of the process zone development. A number of examples of brittle failure of elastic plastic bodies are presented. The initiation and propagation of cracks with the account of plastic properties of materials in the area, near the heated surface are calculated.

Pohreliuk I. M., Yaskiv O. I., Fedirko V. M., Hrypachevskiy O. M., and Proskurniak R. V. Morphology of near-surface layers of Ti–Al–Mo–V alloys after carbonitriding	61
--	----

SUMMARY. The effect of saturating medium composition, temperature and partial pressure of nitrogen on morphology of near-surface layers of Ti–Al–Mo–V alloy after carbonitriding has been investigated. It was shown that morphology of near-surface layers after nitriding and carbonitriding is similar. The near-surface layers consist of the zone of intensive interaction with interstitial elements (nitrogen, carbon) – α -solid solution; transition zone, which is structurally modified and characterized by a more even ratio of α - and β -titanium and, finally, of matrix. It was established that saturating medium composition (nitrogen or nitrogen-carbon mixture) determines the phase-structural changes in near-surface layers, whereas technological conditions of saturation (temperature and nitrogen partial pressure) determine the depth and the level of gas saturation.

Meyer L. W., Kuprin C., and Hahn F. Plastic anisotropy of a ferritic-pearlitic steel at the microstructural scale	66
---	----

Novytskyi V. H., Havryliuk V. P., Panasenko D. D., Kalchuk M. O., and Khoruzhyi V. Ya. The effect of lead on wear resistance and formation of secondary structure of cast Fe–Cr–Cu–Ti–C composites under sliding friction	73
---	----

SUMMARY. The positive influence of lead (2.5%) on initial structure of cast composite (CC) of the system Fe–Cr–Cu–C–Ti, and also on its wear rate, coefficient of friction and formation of secondary structure under dry and boundary friction with lubrication and without it was established.

Stashchuk M. H., Horopatskyi V. H., and Malyk O. M. Modelling of a crack-like cavity with medium by an elongated ellipse	81
--	----

SUMMARY. The influence of the stress field on the electric potential change in the thin elongate elliptic hole filled with a liquid in an elastic metallic body was analytically studied. The solution of the system of Helmholtz equations is the basis of the performed researches that describe distribution of electric potentials in metal, double electric layer and medium. As a result graphic dependences of the electric potential change are built for an elliptic hole filled with a liquid, and also the corresponding displacements of the electrode potential at the liquid and a stressed metal interface were calculated.

FROM THE HISTORY OF FRACTURE MECHANICS DEVELOPMENT

Yarema S. Ya. Formation of the science about metal fatigue. Part 2. 1870–1940	86
---	----

SCIENCE FOR PRODUCTION

Datsyshyn O. P., Tkachov V. I., Hlazov A. Yu., and Khrunyk R. A. Prediction of the contact life of back-up rolls of a rolling mill on the basis of pitting development	95
--	----

SUMMARY. The algorithm of calculational of the near-surface layer residual life of a developed back-up rolls on the basis of pitting development has been worked out in the framework of earlier proposed calculational two-stages model for estimation of rolling bodies contact life under boundary lubrication (friction) conditions. Edge crack growth paths have been constructed and analysed at the stages of shear and opening. The criterion of transition between crack development mechanisms is proposed. The estimation of rolls life is given using characteristics of cyclic crack growth resistance of 9XΦ, GH and SKH roll steels. The contact life has been investigated depending on such operational parameters as friction coefficient between rolling bodies, size of a contact area, value of a contact pressure, inclination angle of an initial mode II crack etc. Experimental tests of contact life have been done on the disk 9XC roll steel specimens. The results of theoretical and experimental researches are compared.

<i>Pokhmurska H., Chervinska N., Student M., and Zadorozhna Kh.</i> The influence of laser melting of electric metallized Fe–Cr–B–Al coatings on their corrosion resistance	106
---	-----

SUMMARY. The influence of surface melting of arc sprayed coatings obtained from cored wires based on FeCrB system, with addition of aluminium, nickel and copper powders to wire charge, by means of Nd:YAG laser irradiation was studied. It was shown that the addition of small amount of these alloying elements to investigated coating system has different effect on the character of formation, microstructure and electrochemical characteristics of modified layers. In particular, copper and nickel increase the wettability of the melted coating. Laser parameters affect strongly the uniformity of their distribution in melted layers. Inhomogeneity of element distribution is stronger in the case of copper addition and can lead to some decrease of corrosion properties of modified coatings. Aluminium increases corrosion resistance of laser modified coatings.

<i>Shyrokov V. V., Vasylenko Yu. I., Khlopyk O. P., and Frenchko M. S.</i> Development of antifriction alloys and compositions based on aluminium for sliding pantographs	111
---	-----

SUMMARY. The influence of aluminium alloying by Cu (2...4%), Si (2...4.5%), Sn (10...15%), Pb (10...15%) on its wear resistance under friction in a couple with Cu wire has been investigated. It was found that alloying increases the wear-resistance of alloys and decreases the contact electric wire wear. Additional decrease of its wear is obtained by the carbon graphite elements in a counter body. Large-scale investigations of metallic trolley-bus insertions with carbon graphite elements showed the greater life to compare with conventional ones (totally carbon graphite): in 5–8 times in dry weather and in 2–3 times in the rainy weather conditions. The wear of copper conductor is minimal.

<i>Sokolov O. D., Mannapova O. V., Kostrzhytskyi A. I., and Olik A. P.</i> Improvement of corrosion resistance of grey cast-iron by ion nitriding	116
---	-----

SUMMARY. Ion nitriding of grey cast-iron for 1.5 h at 550°C increases corrosion resistance of its surface in 1.5–2.1 times.

<i>Kralia V. O., Moliar O. H., Khimko A. M., and Puhachevskyi D. O.</i> Fatigue characteristics of BT22 titanium alloy with wear-resistant coatings	119
---	-----

SHORT REPORTS

<i>Neprila M. V., Stefan V. P., and Chervatiuk V. A.</i> The influence of polyester and isocyanate components on silicon organic compositions hardening	123
---	-----

JUBILEES

<i>Stepan Yarema</i> (to the 80 th birthday)	125
---	-----

List of papers published in “Physicochemical Mechanics of Materials” in 2006	127
--	-----

Authors’ index	131
----------------	-----