

CONTENTS

<i>Panasyuk V. V. M.</i> Savin and formation of the Lviv scientific school on mechanics of materials	7
--	---

<i>Mykhaskiv V. V. and Zhabdynskiy I. Ya.</i> The solution of non-stationary problems for a complex body with cracks by integral equations method	33
---	----

SUMMARY. A problem on the nonstationary loading of a plane crack in a bimaterial solid formed by two ideally bonded elastic half-spaces is considered. In the Fourier time transform domain it is reduced to the boundary integral equations relative to the crack opening functions. Contact conditions are satisfied when deducing the equations. By the numerical solution of equations and determination of originals the temporal dependences of mode-I stress intensity factor in the vicinity of a penny-shaped crack, which is perpendicular to the interface, are obtained for different types of normal dynamic loading and relations between the elastic modules of the composite constituents.

<i>Sokolovskiy Ya. I. and Petriv O. M.</i> Investigation of the stress-strain state of a wood-chip under hot pressing	43
---	----

SUMMARY. Physical and mathematical model for calculation of temperature and humidity and determining of stress and strain under pressing of a chipboard plate for variable action of press is presented. Adequacy of numerical realisation of the model and experimental data is shown. The influence of heat-and-mass transferring fields on stress and strain has been analysed for different stages of press action.

<i>Savruk M. P., Osiechko A. M., and Panasyuk V. Ye.</i> Fracture deformation criterion for bodies with angular notches under longitudinal shear	49
--	----

SUMMARY. The force criterion of fracture is the most wide-spread for evaluating the limit equilibrium of bodies with V-notches. The critical value of the stress intensity factor depends on the notch angle. In the paper the deformation criterion of fracture containing only standard characteristics of the material: yield strength and crack growth resistance is proposed. The criterion is developed on the basis of the closed solution of an elastic – plastic problem for an infinite wedge under longitudinal shear.

<i>Vytvytskyi V. I.</i> Correlation relationships between mechanical characteristics of corrosion-resistant steels	54
--	----

SUMMARY. A stability factor of austenite A_γ for corrosion resistant steels is proposed. It allows of estimate quantitatively their equilibrium phase-structural state by chemical composition. The composition is evaluated on the basis of chromium- and nickel equivalents. A correlation between steel mechanical characteristics σ_B , $\sigma_{0.2}$, δ , and ψ are obtained using a factor A_γ .

<i>Matysiak S., Yevtushenko O., and Kutsiei M.</i> Temperature field during breaking of a massive body with composite coating	61
---	----

SUMMARY. The analytical solution of a non-stationary heat conductivity problem for the piecewise homogeneous body consisting of a semi-space with a composite strip applied on its surface is obtained. The surface of a strip is heated by a thermal flow with the intensity equal to specific capacity of friction at braking. Dependences of temperature on geometrical and physical properties of composite components and substrate are studied.

<i>Malyshev V. V. and Hab H. I.</i> Physicochemical properties of galvanic tungsten carbide and zirconium diboride coatings on steel	68
--	----

SUMMARY. Physicochemical and mechanical properties of tungsten carbide and zirconium diboride galvanic coatings on different materials, obtained by ionic melt electrolysis are discussed. Coatings thickness is up to 100 μm . As a result of applying coatings, the wear resistance of steel specimens increases in 6–9 and 8–11 times respectively, and the abrasion resistance – up to 7–8 and 8–10 times.

<i>Nykyforchyn H. M., Student O. Z., and Markov A. D.</i> Abnormal behaviour of high-temperature degradation of the weld metal of low-alloy steel welded joints	73
---	----

SUMMARY. Integral mechanical properties, such as hardness, impact toughness, tensile properties and local fracture mechanics parameters (static and cyclic crack growth resistance) are sensitive to in service degradation of a weld metal of 15X1M1Φ steel of power plant steam pipeline. Simultaneous decrease of such parameters as: resistance to brittle fracture, hardness and strength is a phenomenon of in service degradation of the weld metal. The specific correlation between ductility properties and other mechanical parameters was established. Particularly the increase of δ_5 of exploited metal agree well with the decrease of its strength level, whereas decrease of ψ agrees with reduction of brittle fracture resistance. Strength and plasticity of exploited weld metal decrease much more to compare to virgin state. The absence of ferrite edging at the boundaries of primary austenitic grains causes the low resistance to brittle fracture, while changes in acicular ferrite – to deterioration of mechanical properties. Ductile fracture of non- exploited metal changes to intercrystalline fracture in the exploited metal.

<i>Prytula A. O., Pohreliuk I. M., and Fedirko V. M.</i> The influence of the degree of rarefication of oxygen in the environment on interaction of boron carbide with titanium alloys	80
--	----

SUMMARY. The mechanism of processes at the interface metal-saturation medium under thermal diffusion saturation of titanium alloys in boron carbide at the temperatures below the point of titanium alloys phase transformation has been described. The influence of the partial pressure of oxygen over the boron carbide dust on the interaction of titanium and saturating medium has been established. The possibility to formation of steady borides coatings on the titanium matrix has been shown.

<i>Humeniuk O. L., Syza O. I., and Krasovskiy O. M.</i> Inhibitor protection of steels in acidic and neutral media by derivatives of 2-mercaptobenzimidazole.....	85
---	----

SUMMARY. The anticorrosion properties of the new synthesised 2-mercaptobenzimidazole derivatives and also the efficiency of their action in the compositions on the basis of the production wastes of ϵ -caprolaktam of Chernihiv plant “Khimvolokno” were studied. The conclusion about the possibility of use of the test compounds as inhibitors of 20 steel corrosion in acidic and neutral media was drawn. The efficiency of application of protective compositions based on the production wastes of ϵ -caprolaktam with 2-mercaptobenzimidazole derivatives in the working media with pH 1...6.5 was shown.

<i>Bulyk I. I., Trostianchyn A. M., and Markovych V. I.</i> Phase transformations in the SmCo ₅ -based alloy induced by hydrogen under pressure up to 650 kPa	94
--	----

SUMMARY. The interaction of the alloy based on SmCo₅ compound with hydrogen was studied by means of the differential thermal analysis and X-ray phase analysis at the initial hydrogen pressures 200; 300; 400; 500; 650 kPa and temperature up to 1233 K. The alloys hydride is formed at a temperature of 343 K; hydrogen desorbs from the alloys hydride phases at 388...408 and 488...523 K; the alloy partially disproportionates into SmH_x and Co at 828...863 K; SmH_x is partially decomposed at 1008...1053 K, SmCo₅ and Sm₂Co₁₇ phases were found; Co, SmCo₅ and Sm₂Co₁₇ phases were observed above 1168...1188 K. The composition of phases depends on the time of the alloy interaction with hydrogen.

INVESTIGATION AND TEST METHODS

<i>Sylovaniuk V. P., Marukha V. I., and Onyshchak N. V.</i> Residual strength of cylindrical elements with cracks healed by injection technology	99
--	----

SUMMARY. The approximate analytic solution of the problem for a crack-like defect in an elastic cylinder is obtained. The level of strengthening of cylindrical element with a crack, when it is filled with injection material is determined. The parameters that define the effectiveness of the strengthening by injection are established. Experimental investigations that prove the theoretical predictions about strengthening of structural element by means of injection technologies are carried out.

SCIENCE FOR PRODUCTION

Timofieiev B. T. and Bazaras Zh. L. Low-cycle fatigue of 08X18H10T steel welded joints104

SUMMARY. The systematized experimental data on low-cycle fatigue strength of 08X18H10T steel and its welds at 20 and 350°C, made by manual electric-arc welding with ЭА-400/10Y electrodes and argon-arc welding with non-melting electrode, applying a wire of Св-04X19H11M3 grade are presented. The obtained data are compared with current standard ПНАЭ Г-7-002-86.

Narivskiy O. E. Micromechanism of corrosion fracture of heat-exchangers plates.....110

SUMMARY. The micromechanism of corrosion fracture of a heat exchanger plates is investigated. Operation of the heat exchanger in the conditions of plates pollution with sediment from water results in local corrosion of plates under the sediment. In identical operating conditions of the heat exchanger the heat-transmitting AiSi316Ti steel plates have operated in 2.36 times longer, than AiSi304L steel plates. Corrosion fracture of plates under the sediment began with origin of pits at nonmetallic inclusions of a certain nature. The pitting was developed into corrosion spots by the mechanism of stress corrosion cracking and hydrogen embrittlement.

Kliakhina N. A., Hru B. A., and Sokolov V. K. Corrosion resistance of nitrified films in sulphate acid117

SUMMARY. Corrosion stability of substrates made of different metals and deposited nitride films has been investigated by a gravimetric method. Potentials and currents of corrosion have been determined. It has been established that nitride films obtained by different methods have a rather high stability in 10% H₂SO₄ solution at ambient temperature.

IN SCIENTIFIC CIRCLES

Stashchuk M. H. Problems of brittle fracture mechanics (scientific seminar)120

Okhota H. H. Corrosion theory and corrosion protection (scientific seminar)121

Vasylyv Kh. B. Theoretical and applied tribology (scientific seminar)123

Defense of theses125

JUBILEES

Ihor Kostiantynovych Pokhodnia (to the 80th birthday)127